

AGRIFARM 
EXPERTISE IN ALL FIELDS



Agricultural Lubricants



Protect your machinery, for a long and reliable life.

The leading OEM supplier in Germany.

Almost nobody understands engines, gearboxes and hydraulic lubrication better than FUCHS.

As the world's largest independent manufacturer of lubricants, we concentrate exclusively on lubricants.

Because we know and understand the technical demands, we can always offer you the best possible product.

For all of your lubricant demands

All the time.

All the lubricants for agricultural fleets.

Greases for vehicle and machinery bearings, hydraulic oils for a variety of applications or engine and gear oils for all the vehicles on your farm and on your fields. With FUCHS you get the perfect lubricant from just one source enabling a rationalisation of oil grades for your entire vehicle and machinery fleet.

Regardless of what FUCHS lubricant you choose: you will benefit from your decision.

Every day.

Your advantages: Lower operating costs and increase reliability.

Lubricants are not just lubricants: Along with ultimate reliability at all temperatures, high-performance lubricants from FUCHS also offer a noticeable reduction in fuel consumption and extended oil change intervals.

The benefits are obvious: More efficient gearboxes and engines results in lower operating costs, simply from decrease down time and lower fuel consumption.

Depending on usage, just 1% less fuel consumption can generate savings of hundreds of dollars per vehicle per year.

Moreover, the use of multi-functional oils (HYDRAMOT) eliminates the risks of using the wrong lubricant because a machine may require just one lubricant. HYDRAMOT can be used in engines, gearboxes and hydraulic systems.*

For us, the operational reliability of your machinery and the protection of your investment is our highest priority.

Products for the most demanding applications:



Engine Oils

Premium

TITAN CARGO SAE 15W-40

Ultra high-performance, fuel-economy oil for a variety of commercial vehicle diesel engines. Specially developed for Volvo with extended service intervals, exhaust after treatment and turbocharger.

Protecting exhaust gas treatment systems with very low sulphated ash levels and low content levels of phosphorus and sulphur.

Excellent wear protection, even under constant full load due to the new additive and base oil technology.

Highest neutralization potential (TBN) in its class. Durable protection against aggressive acids and corrosion during the whole oil drain interval.

Reduced content of heavy metals, minimizes contaminant emissions.

Prevents deposits in the engine and turbocharger due to excellent soot handling properties. This results in high levels of performance, reliability and low maintenance costs.

Rationalization of the newest VOLVO, MACK and RVI engine oil specifications in a single product.

Tested to and recommended by:

- Specifications**
- ACEA E9/E7
 - API CJ-4/CI-4 PLUS/CI-4
 - CAT ECF-2/ECF-3

Approvals

- CUMMINS CES 20081
- DEUTZ DQC III-10 LA
- DETROIT DIESEL DDC 93K218
- MACK EO-O PREMIUM PLUS
- MAN M 3575 / 3275-1
- MB-APPROVAL 228.31
- RENAULT RLD-3
- VOLVO VDS-4

- FUCHS Recommendations**
- ALLISON C-4

Advanced

TITAN UNIVERSAL HD SAE 15W-40

Titan Universal HD is a high performance lubricant for diesel & petrol engines, with and without turbochargers.

Equally suited for highway & construction vehicles

Designed to meet the requirements of European equipment

Contains high detergency level to ensure maximum engine cleanliness and minimal bore polishing or ring sticking

Tested to and recommended by:

- Specifications**
- ACEA A3/B3/B4
 - API CG-4/CF/SL

Approvals

- DEUTZ DQC I-O2
- MAN 271
- MB-APPROVAL 228.1 / 229.1
- MTU DDC TYPE-2

FUCHS Recommendations

- ACEA E2
- MIL-L-2104 E
- ALLISON C-4
- CASE MS 1120
- DAF
- MACK EO-L
- MH 330 G
- SCANIA
- STEYR A-202
- VOLVO VDS
- VW 501 01/505 00

TITAN ULTRALUBE SAE 15W-40

Titan Ultralube is a heavy duty diesel engine oil that has been developed for use under the most arduous conditions in both on and off highway applications.

Titan Ultralube contains an advanced formula that meets the latest API and ACEA specifications

Suitable for European, American & Japanese diesel engines

Unlike most other oils on the market Titan Ultralube allows for product rationalisation as you can eliminate stocking separate oils for American and European engines.

- Specifications**
- ACEA E3/E5/E7/A3/B3/B4
 - API CI-4 SL

FUCHS Recommendations

- CUMMINS CES 76
- VOLVO-VDS-2
- MACK EO-M PLUS
- CAT ECF 1-a
- RENAULT RLD-2
- ZF TE-ML 07C
- MB 228.3, 228.1, 229.1

Specialty

TITAN CARGO MAXX SAE 10W-40

Contains new additive technology and carefully selected synthetic base oils to provide full performance retention for the long term.

Provides further protection to exhaust after treatment systems, shielding against clogging and contamination. Developed for the latest generation of heavy duty European diesel engines in commercial vehicles.

Tested to and recommended by:

- Specifications**
- ACEA E9/E7/E6
 - API CI-4
 - CATERPILLAR ECF-1-a

Approvals

- DEUTZ DQC III-5
- MACK EO-M PLUS
- MAN M 3477
- MB-APPROVAL 228.51 / 235.28
- MTU DDC TYPE 3.1
- RENAULT RXD / RGD
- VOITH-RETARDER
- VOLVO VDS-3 / CNG

FUCHS Recommendations

- CUMMINS CES 20077
- DAF
- MAN M 3277 CRT

Specialty

TITAN CARGO MC SAE 10W-40

Titan CARGO MC is a fully synthetic Ultra high performance lubricant, that was designed to gain extra fuel economy in highly stressed, high rated diesel engines.

Suits all highly stressed diesel engines with and without turbochargers including trucks, buses, agricultural, construction, industrial equipment, vans and cars.

Developed to improve the performance and efficiency of modern logistic and transportation companies by increasing fuel economy

Tested to and recommended by:

- Specifications**
- ACEA E7/E4
 - API CI-4

Approvals

- CUMMINS CES 20077/8
- DEUTZ DQC III-10
- MACK EO-M PLUS
- MAN M 3277
- MB-APPROVAL 228.5 / 235.27
- MTU DDC TYPE-3
- RENAULT RXD/RLD-2
- VOITH-RETARDER "A"
- VOLVO VDS-3

FUCHS Recommendations

- DAF
- IVECO 18-1804
- MAN M 3277CRT
- SDFG OM-1901A




Products for the most demanding applications:



Gear Oils

Premium		Advanced	
TITAN SUPER GEAR 85W-140		TITAN GEAR SYN SAE 80W-140	
<p>TITAN SUPERGEAR 85W-140 is a mineral universal gear oil for use in manual transmissions and axle gearboxes in both passenger cars and commercial vehicles.</p> <p>TITAN SUPERGEAR 85W-140 provides good cold flow properties. This supports easy cold starting and easy shifting in the warm-up period. Improved lubrication and excellent protection against wear even during short-distance winter operation.</p> <p>The good corrosion protection provided by TITAN SUPERGEAR 85W-140 protects against rust and attacking of non-ferrous metals.</p>	<p>Specifications</p> <ul style="list-style-type: none"> • API GL-4 / GL-5 <p>Approvals</p> <ul style="list-style-type: none"> • ZF TE-ML 05A / 12E / 16D <p>FUCHS Recommendations</p> <ul style="list-style-type: none"> • MIL-L-2105 D • PI60033e 	<p>Heavy duty, extreme pressure lubricant that is formulated with a synthetic base stock which provides a high viscosity index & exceptionally low pour point.</p> <p>Proven high & low temperature performance that exceeds conventional 85W-140 hypoid gear lubricants.</p>	<p>Specifications</p> <ul style="list-style-type: none"> • SAE J2360 / MIL-PRF-2105E, MIL-L-2105D • API MT-1. GL-55 <p>Approvals</p> <ul style="list-style-type: none"> • Dana SHAE 429 <p>FUCHS Recommendations</p> <ul style="list-style-type: none"> • ArvinMeritor O-80, O-76-B • Mack GO-J • International TMS 6816
TITAN SUPER GEAR SAE 80W-90			
<p>Hypoid lubricants for highly stressed differentials, crown-wheel & pinion gears, steering mechanisms & distributor drives in vehicles industrial machinery.</p> <p>Provides increased fuel economy & guarantees the perfect function of synchromesh transmissions.</p> <p>Provides rapid oil circulation & contains excellent cold starting properties, while the lubricant film remains stable and maintains performance under very heavy loads.</p>	<p>Specifications</p> <ul style="list-style-type: none"> • API GL-4 / GL-5 <p>Approvals</p> <ul style="list-style-type: none"> • ZF TE-ML 05A / 12E / 16B / 17B / 19B <p>FUCHS Recommendations</p> <ul style="list-style-type: none"> • MIL-L-2105 D 		



Transmission Oils

Premium	New Formulation	Premium	New Formulation
<p>TITAN UTTO</p> <p>TITAN UTTO is a universal tractor transmission oil, ideally suited to agricultural equipment operating under severe load conditions, requiring a common oil for trans-mission, differential, final drives, hydraulics, wet clutches and wet brakes.</p> <p>TITAN UTTO was formulated for use under the most arduous conditions in both on and off highway applications so you can be sure your equipment is always protected.</p>	<p>Specifications</p> <ul style="list-style-type: none"> • API GL-4 • M1129 A, 1127B • M1135, 41, 43, 45 • J20C • M2C48-B, M2C134-D • M2C86-B • FNHA-2-C-201.00 • MS 1205, 06, 07, 09 • KUBOTA UDT • VOLVO VME WB 101 • ZF TE-ML 03, 05, 06 • AGCO / WHITE FARM • Q1826, PF821 XL • CAT TO-2 • ALLISON C-4 	<p>TITAN UTTO PRO</p> <p>High performance multifunctional oil based on specially selected additives and high quality base oils combining improved wear protection and excellent viscosity / temperature characteristics.</p> <p>Specially developed regarding wear protection and low temperature fluidity against the requirements of the latest VCE-Specification WB 102.</p> <p>Perfectly fits axels, gears and final drives with or without wet brakes and differential locks.</p>	<p>Specification</p> <ul style="list-style-type: none"> • API GL-4 • SAE J 306:75W-80 <p>Approval</p> <ul style="list-style-type: none"> • VOLVO WB 101 <p>FUCHS Recommendation</p> <ul style="list-style-type: none"> • ALLISON C-4 • CASE MS 1207/1209/1210 • FORD M2C86-C • FORD M2C134-D • JDM J 20 C / D • KOMATSU AXO 80 (KES 07.866) • KUBOTA UDT • MASSEY FERGUSON CMS 1135 / 1143 • VOLVO WB 102 • ZF-TE ML 03E, 03F, 05F, 06K



Multifunctional Engine Oils

Premium	
<p>TITAN HYDRAMOT</p> <p>TITAN HYDRAMOT is an advanced multi functional universal engine oil. Suitable for use in many engines, gears boxes and hydraulic systems.</p> <p>It was developed for advanced diesel engines with high demands on service intervals and engine cleanliness.</p> <p>Designed for naturally aspirated and turbo-charged engines, manual gearboxes, wet-brake systems, tractor hydraulics, construction equipment & conventional diffs.</p>	<p>Specifications</p> <ul style="list-style-type: none"> • SAE 15W/40 • API CF-4/SF • STOU • CATERPILLAR TO-2 • ZF TE ML 06B / 06C / 07B • MF1144 / M1139 • Allison C4 • API GL-4 (L-20) • JDM J27 • NH 030C • FORD M2C-159B3 • FORD 30 / 40 series

Hydraulic Oil



Premium	Advanced
<p>RENOLIN B HVI PLUS RANGE</p> <p>High performance hydraulic oil series with a high viscosity index that reduces energy consumption.</p> <p>Protects against wear and maintains designed viscosity under a wider operating temperature range.</p>	<p>RENOLIN B PLUS RANGE</p> <p>The Renolin B range is a series of high quality HLP hydraulic oils and CLP lubricating Oils.</p> <p>RENOLIN B series of oils improve resistance to ageing increase service life.</p> <p>They provides extended greasing intervals whilst improving wear & corrosion protection as well as oxidation resistance.</p>

Greases



Premium	Advanced	Specialty
<p>LARGERMEISTER XXL</p> <p>LARGERMEISTER XXL is an all round grease that can be used for lubrication of heavy-loaded plain and roller bearings in all types of earthmoving machines, specially when subjected to severe operating conditions like high loads and elevated temperatures.</p> <p>LARGERMEISTER XXL can be used as universal grease in areas where lithium or lithium complex soap greases are used.</p> <p>In these cases with LARGERMEISTER XXL the re-lubrication intervals can often be increased significantly.</p>	<p>RENOLIT XTB 2</p> <p>Long life multipurpose grease that has been specially designed for extreme bearing applications.</p> <p>Suitable for a variety of automotive applications, including wheel bearing and general chassis lubrication.</p>	<p>RENOLIT HDCE2</p> <p>RENOLIT HD CE2 a high quality heavy duty extreme pressure grease that was specially formulated for earthmoving and construction equipment operating under arduous conditions.</p> <p>RENOLIT HD CE2 grease is especially suited to applications including hammers, bucket pins and bushes and plain bearing applications of excavators, dump trucks and various other applications where parts are subjected to oscillating movements, vibrations and shockloads.</p> <p>Protects against corrosion even under extreme wet conditions.</p>
<p>RENOLIT POLIPLEX</p> <p>RENOLIT POLIPLEX SERIES is an all-round lithium complex grease that represents the most advanced lubricating technology which has been formulated for conditions of extreme pressure & temperature.</p> <p>Also ideal for general purpose applications contains a "tacky additive" that increases water resistance & improves lubrication on worn parts</p>	<p>RENOLIT LEP2HD</p> <p>RENOLIT LEP 2 HD is a heavy duty extreme pressure grease that protects against component wear under severe conditions.</p> <p>Excellent resistance to water washout ensures lubrication is maintained under extremely wet conditions.</p>	

Products for the most demanding applications:

Coolants

Premium		Advanced	
Tested to and recommended by:		Tested to and recommended by:	
<p>MAINTAIN FRICOFIN</p> <p>Long life antifreeze and corrosion inhibitor for all liquid cooled internal combustion engines in cars, vans, trucks, buses, construction and industrial machinery.</p> <p>MAINTAIN FRICOFIN is nitrite, amine and phosphate free as demanded by many European Original Equipment Manufacturers.</p> <p>MAINTAIN FRICOFIN can be used when manufacturers recommend their "own" brand of anti-freeze.</p>	<p>Specifications</p> <ul style="list-style-type: none"> ASTM D 3306-05 ASTM D 4985 AFNOR NF R 15-601 BS 6580:1982 SAE J1034 <p>Approvals</p> <ul style="list-style-type: none"> DEUTZ TR-0199-99-1115 JENBACHER TA 1000-0201 MAN 324 NF MAN 324 NF PRITARDER MB-APPROVAL 325.0 MTU MTL 5048 MWM TR 0199-99-2091 PN-C 40007:2000 VOITH TURBO 172.00225010 <p>FUCHS Recommendations</p> <ul style="list-style-type: none"> BMW N 600 69.0 BOMAG LIEBHERR TLV 035; TLV 23009 A OPEL/GM B 040 0240 VW TL 774-C(G 11) 	<p>MAINTAIN FRICOFIN HDD COOLANT</p> <p>Premium universal fully formulated antifreeze/antiboil coolant premix for all water-cooled engines</p> <p>TITAN HDD COOLANT is a true universal mixed fleet heavy-duty engine coolant for use in all water cooled engines, meets or exceeds requirements of ESI for all major Original Equipment Manufacturers</p> <p>TITAN HDD is available in premix and concentrate</p>	<p>FUCHS Recommendations</p> <ul style="list-style-type: none"> ASTM D-3306, D-4985, D-6210 MAN 324 Caterpillar EC1 MTU MTL 5048 app C Cummins 14603 New Holland WSN-M97B18-D Detroit Diesel 75E 298 PACCAR DaimlerChrysler MS 7170, MS 9769 Peterbilt 8502.002 Ford ESE-M97B44A, ESE-M97B18-C, Ford WSSM97B51-A1 Perkins Freightliner 48-2288D Saab-Scania 6901 GM 1825M, 1899M, GM Heavy Truck SAE J1034, J1941 Hyundai TMC RP 329 JIS K2234 Volvo Heavy Truck (Approved) Kenworth RO26-170-97 White Star Landrover US Federal A-A-870-A MACK Trucks AS 2108-2004 Type A

Cleaners

Premium		Advanced	
Tested to and recommended by:		Tested to and recommended by:	
<p>RENOCLEAN FLEETWASH</p> <p>Renoclean Fleetwash is a detergent based heavy duty vehicle wash with "quick-break" properties.</p> <p>Renoclean Fleetwash was formulated to effectively clean heavy equipment such as dump trucks, cranes, prime movers, trailers, dozers and excavators.</p> <p>Renoclean Fleetwash is highly effective for removing most soils including dirt, mud, grime, oil and soot.</p>	<p>Biodegradable AS 4351.2 ISO 7827</p>	<p>RENOCLEAN ORANGE</p> <p>Renoclean Orange is a quality hand cleaner that has been developed for the effective cleaning of heavily soiled, oily and grease covered hands.</p> <p>Renoclean Orange leaves hands feeling smooth and clean without the greasy feeling that many other cleaners leave behind.</p> <p>The natural citrus, lanolin and coconut oils found in Renoclean Orange help replenish dry cracked skin whilst leaving the skin feeling and smelling refreshed. Renoclean Orange provides a rich creamy lather when worked into the hands.</p> <p>While being gentle on the hands, the beads within Renoclean Orange provides an abrasive aid in the removal of tough oil and grease stains without irritating the skin.</p> <p>Renoclean Orange can be used in all applications where an effective hand cleaner is required, whether it is in a mechanical workshop to an office washroom or even at home.</p>	
<p>RENOCLEAN DEGREASER 9110</p> <p>Renoclean Degreaser 9110 is a solvent based degreasing solution developed to dissolve oil and grease residues.</p> <p>Renoclean Degreaser 9110 is suitable for heavy duty degreasing operations where a versatile solvent based cleaner is required.</p> <p>It does not effect any common metals and is easily removed by rinsing with cold water.</p>			

This guide explains the different lubricants available for your equipment and what the specifications mean.

Engine oils

A variety of different engine oils which fulfil a range of specifications are available. The table here shows what lubricant types are implied by the most important engine oil specifications:

ACEA

The various engine oil applications are characterized by letters following the European ACEA classifications.

ACEA E is for diesel engines in commercial vehicles and thus for tractors, harvesters, etc.

- E1 Became invalid in March 2000
- E2 Normal use / normal intervals / largely based on MB 228.1 and MAN 271
- E3 Heavy-duty use / Euro 1 and 2 / extended intervals possible / largely based on MB 228.3 and MAN M 3275
- E4 Very heavy-duty use / Euro 1, 2 and 3 / extended intervals possible / largely based on MB 228.5 and MAN M 3277
- E5 Heavy-duty use / Euro 1, 2 and 3 / extended intervals possible / performance similar to E3, additional wear test on American engines
- E6 Called low-ash oils with low ash contents for engines fitted with exhaust treatment systems, e.g. diesel particulate filters. Otherwise, the same performance as ACEA E4.
- E7 Follow-on category for E3 and E5 heavy-duty use / Euro 1, 2, 3 and 4 extended intervals possible. For engines fitted with particulate filters and/or exhaust treatment systems.
- E9 Super High Performance Diesel (SHPD) engine oil with SAPS limitations. Recommended for standard oil drain intervals in commercial vehicles with exhaust gas after treatment systems like DPF, EGR and SCR running under severe conditions in combination with low sulphur Diesel fuel.

API

- Diesel engines (C = Commercial): 4-stroke engines**
- API CC No longer valid. For commercial vehicles with older engines (up to about 1985).
- API CD No longer valid. For commercial vehicles with older engines (up to about 1990).

Indirect injection diesel engines

- API CF Especially for diesel engines with indirect injection (swirl chamber). Also suitable for fuel sulphur > 0.5% (Standard exists since 1994).

Direct injection diesel engines

- API CE Heavy-duty and turbocharged diesel engines. Improved characteristics regarding oil consumption, oil thickening, piston coking and wear.
- API CF-4 Surpasses API CE regarding piston coking and oil consumption. For higher-speed diesel engines (Standard exists since 1990).
- API CG-4 For high performance diesel engines and fuel sulphur < 0.5%. Required for engines complying with German 1994 emission regulations.
- API CH-4 Since September 1998, for 1998 emission regulations for trucks in the USA. Surpasses API CG-4.
- API CI-4 Since March 2003, for engine emissions according to TIER II (US exhaust emission regulations), Surpasses CH-4.
- API CI-4+ Introduced in 2004, identifies oils formulated to provide a higher level of protection against soot-related viscosity increase and viscosity loss due to shear in diesel engines.
- API CJ-4 Introduced in 2006 for high speed, four stroke engines emissions designed to meet 2007 model year on-highway exhaust emission standards. Surpasses CI-4 PLUS

Gear oils

A variety of different gear oils which fulfil a range of specifications are available. The table here shows what lubricant types are implied by the most important gear oil specifications:

API Classifications

The American Petroleum Institute (API) has created a gear oil classification system which allows categorization according to application conditions. API gear oil classifications are used internationally.

API Gear Oil Classifications	Operating Conditions	Type of Gearbox
API GL-1	Low bearing loads and sliding speeds. No longer valid.	Axle drives with bevel gears, worm drives, manual gearboxes.
API GL-2	Higher loads than API GL-1. No longer valid.	Worm drives which can be operated with API GL-1 oils.
API GL-3	Moderately high loads and speeds. No longer valid.	Axle drives with bevel gears, manual gearboxes.
API GL-4	High speed/low torque or low speed/high torque. No longer valid.	Manual gearboxes, hypoid axles, axle with slightly off-set pinions.
API GL-5	High speed/shock loads or high speed/ low torque or low speed/high torque. Currently valid.	Hypoid axles, manual gearboxes, axles with considerably off-set pinions.
MT-1	Spur gear, dog-engaged gear boxes	Non-synchromesh manual gear boxes

YOUR NEAREST DISTRIBUTOR IS:

FUCHS LUBRICANTS AUSTRALASIA

Head Office Melbourne

49 McIntyre Road
Sunshine Victoria 3020
Phone: 1800 1800 13
Fax: 1800 1800 14
E-mail: customer.service@fuchs.com.au
www.fuchs.com.au

New Zealand Office

485c Rosebank Road
Avondale, Auckland 1026
Phone: 0800 382 476
Fax: 09 820 3643
E-mail: customer.service@fuchs.com.au
www.fuchs.com.au

